

# INTERIOR STAIN & VARNISH

RESOURCE CODE 1116-Line Gloss

1117-Line Satin

SEPTEMBER 2021

PAGE 1 OF 3



## Description & Uses

Wattyl Colourwood Stain & Varnish is a combined stain and clear finish. It offers the convenience of a single product to achieve the finish of a dual stain and clear system. Colourwood Stain & Varnish is ideal for use on awkward areas, such as louvre doors, as it applies a stain and a clear at the same time, in one easy step. It is also suitable for use on most interior woodwork, built-in furniture and panelling. For extra protection on furniture and woodwork overcoat with Estapol Polyurethane Gloss, Satin or Matt.

## Features & Benefits

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>Convenience of a single product stain and clear varnish</li> <li>Easy application</li> </ul> | <ul style="list-style-type: none"> <li>Suitable for awkward areas where a stain may be difficult to apply</li> <li>Durable finish</li> </ul> |
|---|--|

## Colours & Gloss

Available in a range of standard colours. Refer to the Wattyl Interior Timber Guide.

Gloss and Satin.

## Properties & Performance Guide

Dry & Recoat Times	Surface Dry - 4-6 hours Recoat - 24 hours. Fully Cured - 7 days. Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.
Coverage per Coat	Up to 12 M <sup>2</sup> /L depending on the surface texture, porosity and method of application.
Film Thickness	Wet Film Thickness (WFT) - 83 microns. Dry Film Thickness (DFT) - 32 microns.
Thinning	If required, thin sparingly with Mineral Turps.
Clean Up	Clean up with Mineral Turps away from drains. Soak all used cloths and sanding dust in water after use as they may self-ignite. <b>Protect Our Environment:</b> Do not pour leftover paint down the drain. To dispose of unwanted paint see <a href="http://paintback.com.au">paintback.com.au</a> . Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle containers via recycling programs. Check with your local council first.

INTERIOR  
STAIN & VARNISH

RESOURCE CODE 1116-Line Gloss

1117-Line Satin

SEPTEMBER 2021

PAGE 2 OF 3

## Properties &amp; Performance Guide...Continued

VOC (Volatile Organic Compounds)

VOC < 495g/Litre (Satin).  
VOC < 480g/Litre (Gloss).

## Recommended Substrate Conditions &amp; Preparation

Surfaces are to be suitably prepared in accordance with proper trade practices.

Colourwood Stain & Varnish is suitable for use on all interior woodwork, louvre doors, built-in furniture, skirting boards, and panelling.

Not suitable for use on timber floors as uneven wear due to traffic will result in an uneven colouring.

Not suitable for use on MDF. On MDF, use Colourwood Water Based Stain & Varnish.

**Bare Timber:** Fill any holes or small cracks with a suitable putty matched to the timber colour. **Hint:** A coat of Wattyl Sanding Sealer applied before Colourwood Stain & Varnish will assist in achieving a uniform colour, especially where end grain is encountered.

**Clear Coated Surface:** Where the surface has previously been coated with Estapol Polyurethane Gloss, Satin or Matt, Estapol Xtra Clear Gloss or Satin, or Colourwood Stain & Varnish, it should be lightly sanded and thoroughly cleaned before coating. For unknown finishes, it is recommended to use paint stripper to remove the coating; or alternatively sand back to bare timber before refinishing.

**Painted Surface:** Where the surface has previously been painted, use paint stripper to remove the coating; or alternatively sand back to bare timber before refinishing.

**Stained Surface:** Depending on the type of stain, it may be removed with paint stripper.

**All Surfaces:** The surface to be coated should be thoroughly sanded. Coarse sand with 120 grit paper, then final sand with up to 400 grit paper. Always sand in the direction of the timber grain. Remove all sanding dust. Wipe down with a tack cloth, or a cloth dampened with Mineral Turps and allow to dry. Nail holes or cracks should be filled with a suitable putty in a matching colour. Allow putty to dry according to directions and sand smooth. The final surface should be dry and free from wax, grease and dust.

## Application Guide

Stir well before and during use with a broad paddle reaching to the bottom of the can and lifting until contents are completely mixed.

Always test the colour on an offcut or out of sight area before beginning. Where more than one can of Colourwood Stain & Varnish is required to complete a job, combine all contents of cans in a clean metal or glass container and stir well before using.

Apply an even coat with a quality brush, applicator pad or spray equipment. Always lay-off along the grain to reduce visible brush marks. Allow to dry.

To deepen the colour, apply additional coats of Colourwood Stain & Varnish. Sand lightly and dust off between coats.

Where the desired colour is achieved in one coat, apply 1 or 2 coats of Estapol Polyurethane Gloss, Satin or Matt over the Colourwood Stain & Varnish to achieve the required gloss level and film build for protection.

Avoid applying excessively heavy coats of Colourwood Stain & Varnish.

**Bare Timber:** Apply the first coat thinned 5-10% with Mineral Turps. Allow to dry, sand lightly and dust off. Apply the second coat and any subsequent coats unthinned.

**Clear Coated Surface:** Where the surface has previously been coated with Estapol Polyurethane Gloss, Satin or Matt, Estapol Xtra Clear Gloss or Satin, or Colourwood Stain & Varnish, apply 1 or 2 coats of Colourwood Stain & Varnish as required, lightly sanding and dusting off between coats.

**Frequently handled surfaces:** Apply at least 2 and preferably 3 or more coats. To increase the durability without deepening the colour, the second and subsequent coats should be of Estapol Polyurethane Gloss, Stain or matt in the desired gloss level.

Do not apply when temperature is below 10°C or above 35°C or when humidity is very high.

The temperature must not fall below 10°C during the drying process.

INTERIOR  
STAIN & VARNISH

RESOURCE CODE 1116-Line Gloss

1117-Line Satin

SEPTEMBER 2021

PAGE 3 OF 3

## Additional Data

Available in 500ml and 1L sizes.  
Do not apply Estapol Flooring 7008 over Colourwood Stain & Varnish or vice versa.  
Not suitable for use on timber floors as uneven wear due to traffic will result in an uneven colouring.  
Not suitable for exterior use. On exterior timber, use Wattyl Weathergard 2-in-1 Stain & Varnish.  
Containers must be secured and stored upright during transit.  
Containers must not be exposed to excessive heat or cold.  
Store in a secure, cool and well ventilated place. Keep container tightly closed.  
The use of proprietary additives other than those manufactured by Wattyl is not recommended.  
Do not use for any other purpose other than as specified in our literature.

## Safety Data

## First Aid Instructions

For advice, contact the Poisons Information Centre on 131 126 (Australia), 0800 764 766 (New Zealand), or a doctor.  
If swallowed, do not induce vomiting. Give a glass of water to drink.  
If in eyes, wash out immediately with water. Remove contact lenses if present and easy to do so, continue rinsing.  
If inhaled remove from contaminated area to fresh air.  
If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.

## Safety Directions

FLAMMABLE.  
HAZARDOUS: Contains liquid hydrocarbons.  
Keep away from sources of ignition.  
No smoking.  
Keep closed when not in use.  
Keep out of reach of children.  
Avoid contact with skin and eyes.  
Ensure adequate ventilation during use.  
Avoid prolonged breathing of vapour.  
Wash hands thoroughly after use.

## Further Information

For the latest information refer to the Safety Data Sheet available on our websites.  
Australia: [www.wattyl.com.au](http://www.wattyl.com.au) or contact Wattyl Assist on 132 101.  
New Zealand: [www.wattyl.co.nz](http://www.wattyl.co.nz) or contact Wattyl Assist on 0800 825 7727.

1. This information is provided with respect to the listed Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand products. Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand, hereon referred to as "Hempel (Wattyl)," recommends that:

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Hempel (Wattyl); (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the TDS was prepared using information gathered during product development. While Hempel (Wattyl) endeavour to update this information and maintain the accuracy of its contents, Hempel (Wattyl) cannot guarantee that the information is wholly comprehensive.

3. Hempel (Wattyl) recommend that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest office of Hempel (Wattyl).

4. To the full extent permitted by law, the liability of Hempel (Wattyl) for breach of a condition or warranty implied into the contract for sale between Hempel (Wattyl) and you by law is limited at the election of Hempel (Wattyl) to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

All brands and product names are registered trademarks of Hempel (Wattyl) Australia Pty Ltd ABN 40 000 035 914 and Hempel (Wattyl) New Zealand Pty Ltd 942 904 073 3692.

WATTYL ASSIST: Ph: 132 101 (AUSTRALIA)  
Ph: 0800 825 7727 (NEW ZEALAND)