

## EASYFLOOR CLEAR

RESOURCE CODE 811390

NOVEMBER 2024

PAGE 1 OF 3



## Description &amp; Uses

Estapol Easyfloor Clear Finish is a tough, water-based one pack, gloss finish which has been specifically designed to beautify, protect and preserve interior timber, parquet and cork flooring. Combining ease of application with quick drying properties, this water-based floor finish enables timber and cork floors to be clear finished within a day.

Easyfloor Clear Finish is suitable for use on other general interior timber and cork surfaces.

## Features &amp; Benefits

- Low Odour
- Fast drying
- Good abrasion and scuff resistance
- Non-yellowing
- Smooth Gloss Finish

## Colours &amp; Gloss

Clear.

Gloss.

## Properties &amp; Performance Guide

Dry & Recoat Times	Surface Dry - 30 minutes Recoat - 3 hours Fully Cured - 72 hours Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.
Coverage per Coat	Up to 10-14 M <sup>2</sup> /L depending on the surface texture, porosity and method of application.
Film Thickness	Wet Film Thickness (WFT) - 80 microns minimum Dry Film Thickness (DFT) - 25 microns minimum
Thinning	If required, thin up to 5% water.
Clean Up	Clean up with cold water away from drains. <b>Protect Our Environment:</b> Do not pour leftover paint down the drain. To dispose of unwanted paint, visit <a href="http://wattyl.co.nz">wattyl.co.nz</a> . Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle containers via recycling programs. Check with your local council first.
VOC (Volatile Organic Compounds)	VOC < 28g/Litre.

## EASYFLOOR CLEAR

RESOURCE CODE 811390

NOVEMBER 2024

PAGE 2 OF 3

**Recommended Substrate Conditions & Preparation**

Surfaces are to be suitably prepared in accordance with proper trade practices.

**New Timber and Cork Surfaces:** Ensure surface to be coated is thoroughly dry, and free from dirt, grease and wax. Fill all nail holes and cracks in timber with a suitable Timber Putty. Sand all new timber and cork surfaces to a smooth finish and vacuum floor thoroughly to remove all dust.

**Surfaces Previously Coated with Clear Finishes:** Fill all nail holes and cracks in timber with a suitable Timber Putty. Sand the entire surface thoroughly, ensuring that no gloss remains. On aged timber floors, mechanical sanding is recommended, to ensure that satisfactory adhesion is achieved. Vacuum thoroughly to remove all dust.

**Application Guide**

Apply 3 full even coats using a paint pad or a suitable brush.

Use the brush to cut in around the skirting boards, corners, edges etc.

Use a "moving puddle" technique to apply.

Pour an amount of product onto the floor and use the paint pad or applicator to move product around, using a mopping motion. Ensure that the floor has a smooth even coating, and always finish with strokes along the grain. Do not apply excessively heavy coats.

Subsequent coats will result in a higher gloss level and film build. Sand lightly between the 1st and 2nd coats to remove any raised grain using 240 grit sandpaper. Sanding should not be required between additional coats.

Do not apply when temperature is below 10°C or above 35°C or when humidity is very high.

The temperature must not fall below 10°C during the drying process.

**Maintenance**

Sweep floors regularly. Clean with a soft mop and household detergent in warm water.

**Additional Data**

Available in 1 & 4 litre containers.

Under normal drying conditions (20°C) Easyfloor Clear Finish is touch dry in 30 minutes and can be recoated in 3 hours. In cooler conditions, white streaks may be noticed during drying. Do not recoat until these streaks have completely disappeared.

Floors may be subjected to light traffic 24 hours after applying the finishing coat and will be completely cured in 72 hours.

Wattyl do not recommend the staining of timber floors, as staining may highlight surface imperfections.

Do not apply this product by spray or roller.

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold.

Store in a secure, cool and well-ventilated place. Keep container tightly closed.

The use of proprietary additives other than those manufactured by Wattyl is not recommended.

Do not use for any other purpose other than as specified in our literature.

## EASYFLOOR CLEAR

RESOURCE CODE 811390

NOVEMBER 2024

PAGE 3 OF 3

## Safety Data

## First Aid Instructions

For advice, contact the Poisons Information Centre on 131 126 (Australia), 0800 764 766 (New Zealand), or a doctor.  
If swallowed, do not induce vomiting. Give a glass of water to drink.  
If in eyes, wash out immediately with water.  
If inhaled remove from contaminated area to fresh air.  
If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.

## Safety Directions

Keep out of reach of children.  
Avoid contact with skin and eyes.  
Ensure adequate ventilation during use.  
Avoid prolonged breathing of vapour.  
Wash hands thoroughly after use.

## Further Information

For the latest information refer to the Safety Data Sheet available on our websites.  
Australia: [www.wattyl.com.au](http://www.wattyl.com.au) or contact Wattyl Assist on 132 101.  
New Zealand: [www.wattyl.co.nz](http://www.wattyl.co.nz) or contact Wattyl Assist on 0800 825 7727.

1. This information is provided with respect to the listed Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand products. Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand, hereon referred to as "Hempel (Wattyl)," recommends that:

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Hempel (Wattyl); (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the TDS was prepared using information gathered during product development. While Hempel (Wattyl) endeavour to update this information and maintain the accuracy of its contents, Hempel (Wattyl) cannot guarantee that the information is wholly comprehensive.

3. Hempel (Wattyl) recommend that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest office of Hempel (Wattyl).

4. To the full extent permitted by law, the liability of Hempel (Wattyl) for breach of a condition or warranty implied into the contract for sale between Hempel (Wattyl) and you by law is limited at the election of Hempel (Wattyl) to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

All brands and product names are registered trademarks of Hempel (Wattyl) Australia Pty Ltd ABN 40 000 035 914 and Hempel (Wattyl) New Zealand Pty Ltd 942 904 073 3692.

WATTYL ASSIST: Ph: 132 101 (AUSTRALIA)  
Ph: 0800 825 7727 (NEW ZEALAND)