

ULTRA PREMIUM
FISHOILENE

RESOURCE CODE 114312

SEPTEMBER 2021

PAGE 1 OF 3



Description & Uses

Wattyl Killrust Fishoilene is a deodorised fish oil containing rust inhibitor formulated to provide a protective coating for metal. Killrust Fishoilene dries slowly, thus penetrating the rust before gradually setting to a pliable protective coating. Killrust Fishoilene penetrates scale and creeps into crevices and other inaccessible places where corrosion is likely to be most active. Wattyl Fishoilene is designed principally for use in areas where correct surface preparation is not possible.

Features & Benefits

- Fish oil containing rust inhibitor
- Dries slowly to penetrate rust

Properties & Performance Guide

Dry & Recoat Times	Surface Dry - Semi drying only. Allow 48 hours to dry. Recoat - <u>Not recommended for overcoating</u> Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.
Coverage per Coat	Up to 12 M ² /L depending on the surface texture, porosity and method of application.
Film Thickness	Wet Film Thickness (WFT) - 20 microns minimum Dry Film Thickness (DFT) - 15 microns minimum
Thinning	Not required.
Clean Up	Clean up with Mineral Turps away from drains. Soak all used cloths in water after use as they may self-ignite. Protect Our Environment: Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first.
VOC (Volatile Organic Compounds)	VOC < 235g/L (Can)

ULTRA PREMIUM
FISHOILENE

RESOURCE CODE 114312

SEPTEMBER 2021

PAGE 2 OF 3

Recommended Substrate Conditions & Preparation

Surfaces are to be suitably prepared in accordance with proper trade practices.

Suitable for direct application over rusted surfaces such as structural steel, gates, railings, welds, pipes, bolts, screws, rivets and other metal surfaces.

Remove all loose rust scale, peeling or flaking paint by wire brush. Remove grease, oil, dust or dirt by washing with mineral turps and allow to dry.

Do not apply to damp or wet surfaces.

Application Guide

Aerosol: Shake can for a full minute before use **after** hearing the mixing pellet rattle, and from time to time during use.

Apply only outdoors or in a well ventilated area.

Protect nearby surfaces from overspray by covering or masking.

For best results spray at room temperature.

Hold the can upright approximately 25cm from the surface and maintain this distance during application. Spray with slow even strokes. Begin and end each stroke beyond the surface being painted.

Apply sufficient Killrust Fishoilene to completely saturate the rust present.

If the spray jet becomes blocked, remove and clean the jet with fine wire and mineral turps. Do not insert sharp objects into the valve opening of the can.

After use, turn the aerosol upside down and spray until the valve is clear of paint. Wipe the nozzle clean.

Can: Stir well before and during use with a broad paddle reaching to the bottom of the can and lifting until contents are completely mixed.

Apply liberally by brush, roller, spray or dipping, completely saturating the affected area.

Avoid painting when air temperature is below 10°C or above 35°C or when humidity is very high.

In exterior application avoid painting when rain or dew is likely.

Additional Data

Available in 500ml, 1L, 4L and 300g Aerosol.

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold.

Store in a secure, cool and well ventilated place. Keep container tightly closed.

The use of proprietary additives other than those manufactured by Wattyl is not recommended.

Do not use for any other purpose other than as specified in our literature.

ULTRA PREMIUM
FISHOILENE

RESOURCE CODE 114312

SEPTEMBER 2021

PAGE 3 OF 3

Safety Data

First Aid Instructions	For advice, contact the Poisons Information Centre on 131 126 (Australia), 0800 764 766 (New Zealand), or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If inhaled remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.
Safety Directions	FLAMMABLE. HAZARDOUS: Contains liquid hydrocarbons. Keep away from sources of ignition. No smoking. Keep closed when not in use. Keep out of reach of children. Avoid contact with skin and eyes. Ensure adequate ventilation during use. Avoid prolonged breathing of vapour. Wash hands thoroughly after use.
Further Information	For the latest information refer to the Safety Data Sheet available on our websites. Australia: www.wattyl.com.au or contact Wattyl Assist on 132 101. New Zealand: www.wattyl.co.nz or contact Wattyl Assist on 0800 825 7727.

1. This information is provided with respect to the listed Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand products. Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand, hereon referred to as "Hempel (Wattyl)," recommends that:

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Hempel (Wattyl); (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the TDS was prepared using information gathered during product development. While Hempel (Wattyl) endeavour to update this information and maintain the accuracy of its contents, Hempel (Wattyl) cannot guarantee that the information is wholly comprehensive.

3. Hempel (Wattyl) recommend that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest office of Hempel (Wattyl).

4. To the full extent permitted by law, the liability of Hempel (Wattyl) for breach of a condition or warranty implied into the contract for sale between Hempel (Wattyl) and you by law is limited at the election of Hempel (Wattyl) to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

All brands and product names are registered trademarks of Hempel (Wattyl) Australia Pty Ltd ABN 40 000 035 914 and Hempel (Wattyl) New Zealand Pty Ltd 942 904 073 3692.

WATTYL ASSIST: Ph: 132 101 (AUSTRALIA)
Ph: 0800 825 7727 (NEW ZEALAND)