

PROFESSIONAL
NATURAL TEAK OIL

RESOURCE CODE 119905

SEPTEMBER 2021

PAGE 1 OF 3



Description & Uses

Wattyl Natural Teak Oil when used with Estapol Polyurethane Matt will produce a natural oil finish on teak and other timbers. It is designed to impart a very smooth feel to the finish. It is an oil finishing system for new timber or to rejuvenate previously sealed timber.

Features & Benefits

- Produces an attractive, smooth natural oil finish
- Duplicates the finish applied to Danish style furniture and interior décor

Colours & Gloss.

Clear.

Matt.

Properties & Performance Guide

Dry & Recoat Times	Surface Dry	- 12 hours
	Recoat	- N/A.
Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.		
Coverage per Coat	Up to 20 M ² /L depending on the surface texture, porosity and method of application.	
Film Thickness	Wet Film Thickness (WFT)	- 2 microns.
	Dry Film Thickness (DFT)	- 0.5 microns.
Thinning	Not required.	
Clean Up	Clean up with Mineral Turps away from drains. Soak all used cloths and sanding dust in water after use as they may self-ignite. Protect Our Environment: Do not pour leftover paint down the drain. To dispose of unwanted paint see paintback.com.au . Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle containers via recycling programs. Check with your local council first.	
VOC (Volatile Organic Compounds)	VOC < 610g/Litre.	

PROFESSIONAL NATURAL TEAK OIL

RESOURCE CODE 119905

SEPTEMBER 2021

PAGE 2 OF 3

Recommended Substrate Conditions & Preparation

Surfaces are to be suitably prepared in accordance with proper trade practices.

Natural Teak Oil is suitable for use on interior domestic furniture, plywood panelling, lining boards, office furniture, staircase handrails, shop fittings etc.

Ideal for rejuvenating previously sealed furniture.

Not suitable on surfaces treated with a wax finish.

Bare Timber: Fill any holes or cracks with a suitable putty matched to the timber colour. Coarse sand the surface with 120 grit paper, then final sand with up to 400 grit paper. Remove all sanding dust. The surface should be dry and free from wax, grease and dust. Apply 2 coats of Wattyl Estapol Polyurethane Matt.

Clear Coated Surface: If existing coating is unknown, use a paint stripper to remove coating. Fill any holes or cracks with a suitable putty matched to the timber colour. Coarse sand the surface with 120 grit paper, then final sand with up to 400 grit paper. Remove all sanding dust. The surface should be dry and free from wax, grease and dust. Apply 2 coats of Wattyl Estapol Polyurethane Matt.

Stained or Painted Surface: Use a paint stripper to remove some of the existing stain, depending on the type, or all of the existing paint. Fill any holes or cracks with a suitable putty matched to the timber colour. Coarse sand the surface with 120 grit paper, then final sand with up to 400 grit paper. Remove all sanding dust. The surface should be dry and free from wax, grease and dust. Apply 2 coats of Wattyl Estapol Polyurethane Matt.

Application Guide

Stir thoroughly prior to use and regularly during use.

Stain if required with Wattyl Craftsman Traditional Stain or Wattyl Colourwood Interior Stain. Allow to dry according to directions.

Apply 2 coats of Wattyl Estapol Polyurethane Matt at 12 hour intervals then allow 48 hours to dry. Lightly sand along the grain with fine sandpaper, exercising care with edges, mouldings etc. Wipe off all dust with a tack cloth.

Wet the surface with Natural Teak Oil and, while wet, rub vigorously along the grain with a non-soaped household steel wool pad until uniformly smooth. Remove surplus oil with a soft, clean cloth.

To rejuvenate oil finished and previously sealed timber, apply Natural Teak Oil with a soft cloth and, while wet, rub vigorously along the grain. Wipe clean with a soft, clean cloth.

Do not apply when temperature is below 10°C or above 35°C or when humidity is very high.

The temperature must not fall below 10°C during the drying process.

Additional Data

Available in 500ml & 1 litre containers.

Avoid exposure to steam and condensation for 48 hours after application.

Leave 7 days after application before washing. Wash using a sponge or soft cloth with warm water and mild detergent.

Avoid harsh scrubbing and strong household cleaners.

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold.

Store in a secure, cool and well ventilated place. Keep container tightly closed.

The use of proprietary additives other than those manufactured by Wattyl is not recommended.

Do not use for any other purpose other than as specified in our literature.

PROFESSIONAL
NATURAL TEAK OIL

RESOURCE CODE 119905

SEPTEMBER 2021

PAGE 3 OF 3

Safety Data

First Aid Instructions	For advice, contact the Poisons Information Centre on 131 126 (Australia), 0800 764 766 (New Zealand), or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. Remove contact lenses if present and easy to do so, continue rinsing. If inhaled remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.
Safety Directions	FLAMMABLE. HAZARDOUS: Contains liquid hydrocarbons. Keep away from sources of ignition. No smoking. Keep closed when not in use. Keep out of reach of children. Avoid contact with skin and eyes. Ensure adequate ventilation during use. Avoid prolonged breathing of vapour. Wash hands thoroughly after use.
Further Information	For the latest information refer to the Safety Data Sheet available on our websites. Australia: www.wattyl.com.au or contact Wattyl Assist on 132 101. New Zealand: www.wattyl.co.nz or contact Wattyl Assist on 0800 825 7727.

1. This information is provided with respect to the listed Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand products. Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand, hereon referred to as "Hempel (Wattyl)," recommends that:

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Hempel (Wattyl); (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the TDS was prepared using information gathered during product development. While Hempel (Wattyl) endeavour to update this information and maintain the accuracy of its contents, Hempel (Wattyl) cannot guarantee that the information is wholly comprehensive.

3. Hempel (Wattyl) recommend that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest office of Hempel (Wattyl).

4. To the full extent permitted by law, the liability of Hempel (Wattyl) for breach of a condition or warranty implied into the contract for sale between Hempel (Wattyl) and you by law is limited at the election of Hempel (Wattyl) to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

All brands and product names are registered trademarks of Hempel (Wattyl) Australia Pty Ltd ABN 40 000 035 914 and Hempel (Wattyl) New Zealand Pty Ltd 942 904 073 3692.

WATTYL ASSIST: Ph: 132 101 (AUSTRALIA)
Ph: 0800 825 7727 (NEW ZEALAND)