

Taubmans Tradex Ultra Low Sheen Vinyl

Page 1 of 3

DESCRIPTION

- A durable vinyl finish with excellent opacity and very low side sheen to visibly mask substrate imperfections.

PRINCIPAL CHARACTERISTICS

- Ideal for walls in living rooms and bedrooms.
- Ideal for ceilings
- Formulated to resist dirt and scuffing.
- Excellent coverage with minimal roller splatter.
- Dries quickly to a smooth even finish.
- Low odour.

COLOURS AND GLOSS

- Colour – White, may be tinted to a range of pastel colours
- Finish - Ultra Low Sheen (gloss at 60° <5%)

BASIC DATA

- **Surface dry** Thirty (30) minutes at 20°C and 65% relative humidity.
- **Recoat** Two (2) hours at 20°C and 65% relative humidity. Allow up to twice as long for cooler and more humid conditions.
- **Fully cured** Seven (7) days.
All figures are quoted at 20°C and 65% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** 12-14m²/L (depending on porosity and texture of substrate).
- **WFT per coat** 75μ
- **DFT per coat** 30μ
- **Thinning** Clean Water
- **Clean Up** Thoroughly clean all equipment with water, away from drains.
- **VOC** 15g/L as per EC-07-09. VOC (Volatile Organic Compounds).

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- Ensure all surfaces are clean and dry.
- Remove grease, dust and dirt by washing down with detergent and warm water.
- If mould is present treat with a proprietary mould killer and rinse off.
- All loose, peeling and flaking material or rust must be removed with a scraper or wire brush. Sand the surface smooth and remove all dust.
- Fill nail holes and cracks with a proprietary filler as per the manufacturer's instructions. Finish sand the surface to a very high standard and remove all dust.
- Old glossy surfaces must be sanded to a dull finish using 180-220 grit sand paper before repainting. Apply the appropriate sealer system and allow to dry before sanding slightly.

Bare Timber: Taubmans Tradex Oil Based Undercoat, Taubmans Tradex Acrylic Primer Undercoat or Taubmans Easyflo QD Undercoat.

MDF: Taubmans Tradex Acrylic Primer Undercoat.

Bare GIB®: Taubmans Tradex High Build Undercoat, Taubmans Tradex Easy Sand Sealer Undercoat or Taubmans Tradex Pigmented Sealer

Sun burnt GIB®, GIB® Aqualine and Service Areas: Taubmans Tradex Pigmented Sealer.

Fibrous plaster, skim coated surfaces: Taubmans Tradex Pigmented Sealer.

Previously Painted Surfaces (poor condition): Prepare as outlined above and undercoat accordingly.

Previously Painted Surfaces (good condition): Sand and directly apply.

Additional Notes:

- Do not apply when the temperature is below 10°C or if the humidity is greater than 85%.
- Not recommended for use in wet areas e.g. kitchens, laundries and bathrooms. In these areas use Taubmans Tradex Satin Enamel or Taubmans Tradex Flat Enamel.

INSTRUCTIONS FOR USE

- Stir paint thoroughly with a flat stirrer until contents are uniform and thoroughly mixed.
- Thin with up to 5% water if required.
- Apply 2 coats to the surface by airless spray, roller or brush. Recommended tip size for airless spray is 17-19 thou.
- Provide adequate ventilation during use.

SAFETY DATA

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid:**
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 0800 764766 (New Zealand).
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- Available in 4L and 10L containers.

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:

(a) The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. (b) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (c) the product be used only in accordance with the information provided by Wattyl; (d) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (e) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.


Wattyl (N.Z.) Limited, P. O. Box 1545, Auckland, 1.

Phone 09 820 6700

Fax 09 820 6572

WATTYL (NZ) LTD

INFORMATION HELP LINE: 0800 735551 (New Zealand)



-
- When spraying large confined areas e.g. house lots, it is recommended to break the masking after each coat to allow circulation and ensure positive drying. Alternatively place a dehumidifier in the room after all spraying has been completed.
 - All sanding dusts can be harmful. When sanding any surface wear an appropriate dust mask. Avoid breathing the dust.
 - For product advice and assistance telephone toll free 0800 735 551.
-

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:

(a) The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. (b) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (c) the product be used only in accordance with the information provided by Wattyl; (d) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (e) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

Wattyl (N.Z.) Limited, P. O. Box 1545, Auckland, 1.

Phone 09 820 6700

Fax 09 820 6572

WATTYL (NZ) LTD

INFORMATION HELP LINE: 0800 735551 (New Zealand)

