

Taubmans Tradex Pigmented Sealer

Page 1 of 2

DESCRIPTION

- A penetrating sealer for interior and exterior use on porous and powdery surfaces.

PRINCIPAL CHARACTERISTICS

- For use on aged set plaster, fibrous plaster and plaster mouldings.
- Fibre cement, brick, cement render or other masonry surfaces.
- Aged or sunburnt paper-faced plasterboard, paper-faced plasterboard designed for wet areas and wallpaper.
- Penetrates and binds loose or unsound surfaces.
- Seals water stains.
- Will accept acrylic or enamel finishes.
- Especially recommended for skim plastered surfaces.

COLOURS AND GLOSS

- Colour – White
- Finish - Flat

BASIC DATA

- **Surface dry** Four (4) hours at 25°C and 50% relative humidity.
- **Recoat** Twenty – four (24) hours at 25°C and 50% relative humidity. Allow longer for cooler and more humid conditions.
- **Fully cured** Seven (7) days.
All figures are quoted at 20°C and 65% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** 8-14m²/L (depending on porosity and texture of substrate).
- **WFT per coat (average)** 80μ
- **DFT per coat (average)** 45μ
- **Thinning** Mineral Turpentine.
- **Clean Up** Thoroughly clean all equipment with mineral turpentine, away from drains.
- **VOC** >300g/L as per EC-07-09. VOC (Volatile Organic Compounds). Calculations are based on APAS definition and are in accordance with the Green Building Council requirement.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- Remove old flaking paint – use a scraper, wire brush, heat gun and/or sand as necessary. Fill holes and cracks with a suitable filler and allow to fully dry.
- If wallpaper has been stripped, all wallpaper paste should be removed.
- Thoroughly sand glossy surfaces with 180-220 grit sandpaper prior to painting.
- Allow new plaster to dry for 7 days, sand and dust off with a smooth brush, wipe with a damp cloth.
- Ensure all surfaces are clean before proceeding.

Additional Notes:

- Do not apply when the temperature is below 10°C, the humidity is greater than 85%.
- This is a penetrating sealer and does not replace the need for an undercoat.

INSTRUCTIONS FOR USE

- Stir paint thoroughly with a flat stirrer until contents are uniform and thoroughly mixed.
- Thin with up to 10% mineral turpentine if required. Apply by brush or roller. May be applied by spray, but this method is less successful in working the material into a loose surface.
- Provide adequate ventilation during use.

SAFETY DATA

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.
- **S.D.S.** A Safety Data Sheet (S.D.S.) is available on request.
- **First Aid:**
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 0800 764766 (New Zealand).
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- Available in 4L and 10L containers.
- All sanding dusts can be harmful. When sanding any surface wear an appropriate dust mask. Avoid breathing the dust.
- For product advice and assistance telephone toll free 0800 825 7727.

1. This information is provided with respect to the listed Valspar products. Valspar recommends that:

(a) The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current; (b) you review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (c) the product be used only in accordance with the information provided by Valspar; (d) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (e) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy and currency of its contents, Valspar cannot guarantee that the information provided is wholly comprehensive.

3. Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar Office.

4. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.

Valspar Paint (NZ) Ltd, PO Box 1545, Shortland St, Auckland 1140

Phone 09 820 6700