

PREMIUM
PREP+CEILING SURFACE PRO FLAT

RESOURCE CODE 43121239

NOVEMBER 2019

PAGE 1 OF 3



Description & Uses

Wattyl Ultra Prep+Ceiling Surface Pro Flat is a high opacity, high build, acrylic base/ceiling finish coat. Surface Pro Flat is especially formulated for use as part of a Level 5 finish on interior paper-faced plasterboard surfaces. For ceiling applications where a flat finish is desired, Wattyl Ultra Prep+Ceiling Surface Pro Flat is both a sealer and flat finish coat.

Features & Benefits

- | | |
|---|---|
| <ul style="list-style-type: none">• Flat finish• Dual purpose• Time saving• Fast, easy application | <ul style="list-style-type: none">• High opacity• High build• Smooth finish• Formulated for use as part of a Level 5 finish on paper-faced plasterboard. |
|---|---|

APPLICATION IS BY TRAINED APPLICATORS ONLY, FOR FURTHER ADVICE CONTACT YOUR WATTYL REPRESENTATIVE.

Colours

White – Can be tinted to white base colours. Due to the special nature of this product, tinted colours may appear different than the standard colour.

Flat (Gloss level <3 at 60 degrees).

Environmental Data & Certifications



Approved to Australia Paint Approval Scheme Specification APAS 0172.



Verified to the Environmental Choice New Zealand (ECNZ) Specification EC-07-18.

PREMIUM PREP+CEILING SURFACE PRO FLAT

RESOURCE CODE 43121239

NOVEMBER 2019

PAGE 2 OF 3

Properties & Performance Guide

Dry & Recoat Times	Surface Dry - 1 hour Recoat - 2 hours Fully Cured - 7 days Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.
Coverage per Coat	Up to 3-5 M ² /L depending on the surface texture, porosity and method of application.
Film Thickness	Wet Film Thickness (WFT) - 350 microns minimum Dry Film Thickness (DFT) - 150 microns minimum
Thinning	Thinning is generally not required. Thin up to 50% with clean water only when making repairs.
Clean Up	Clean up with cold water away from drains. Protect Our Environment: Do not pour leftover paint down the drain. To dispose of unwanted paint see paintback.com.au . Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle containers via recycling programs. Check with your local council first.
VOC (Volatile Organic Compounds)	VOC < 16g/Litre.

Recommended Substrate Conditions & Preparation

Surfaces are to be suitably prepared in accordance with proper trade practices.

Ensure the surface is clean, dry and free from dust, dirt and grease. All loose, peeling or flaking material must be removed. Fill holes and cracks with a suitable filler and sand lightly to an even finish.

Paper-faced plasterboard: Ensure that the boards have been installed in accordance with the manufacturer's instructions and that all joints are prepared to a smooth, level finish, free of tool marks and ridges; and that the boards are finished to the specified level. Do not sand the uncoated paper-faced plasterboard.

Timber: Ensure the surface is clean and dry. Fill any holes, cracks or surface imperfections with a suitable filler, referring to the manufacturer's instructions regarding priming if required before application of the filler. Sand thoroughly in the direction of the timber grain before wiping down to remove sanding dust.

If mould is present, clean surface with household bleach then rinse well with clean water.

Application Guide

Stir paint thoroughly with a flat stirrer until contents are uniform and thoroughly mixed.

This product is recommended for airless spray application only.

Apply to a properly prepared surface as cross hatch applications wet on wet.

Suggested spray settings for paper-faced plasterboard: 5-21 thou tip at 3000psi.

Suggested spray settings for timber: 3-13 thou tip at 3000psi. (These settings will reduce texture which will cut down on sanding).

Application is by trained applicators only, for further advice contact your Wattyl representative.

For walls and areas other than ceilings apply appropriate Wattyl coatings as the finish coats by brush, roller, or spray.

Do not apply when temperature is below 10°C or above 35°C or when humidity is very high.

Surface Type	Preparatory Coats
New paper-faced plasterboard	Apply cross hatch applications wet-on-wet of Wattyl Ultra Prep+Ceiling Surface Pro Flat.
Bare timber and MDF	Apply cross hatch applications wet-on-wet of Wattyl Ultra Prep+Ceiling Surface Pro Flat. On tannin rich timbers first apply one coat of Wattyl Ultra Prep Primer Sealer Undercoat.

PREMIUM
PREP+CEILING SURFACE PRO FLAT

RESOURCE CODE 43121239

NOVEMBER 2019

PAGE 3 OF 3

Surface Type...Continued	Preparatory Coats...Continued
Bare plaster	Apply one coat of Wattyl Master Prep Pigmented Sealer or Wattyl Acrylic Plaster Sealer.
For surfaces other than those nominated contact Wattyl Assist to determine the most suitable preparation prior to painting.	

Additional Data

Available in 10 & 15 litres.

Tinted paint is non-refundable, so choose your colours carefully.

If this paint has been tinted, check that the colour is suitable for your requirements before application. For best results and colour consistency, tinted paint should be boxed and thoroughly mixed on site.

For ceilings in wet areas or where a washable ceiling finish is required, use Wattyl Ultra Interior Low Sheen Acrylic or Wattyl Ultra Interior Satin Acrylic.

Avoid exposure to steam and condensation for 48 hours after application of the final coat.

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold.

Store in a secure, cool and well ventilated place. Keep container tightly closed.

The use of proprietary additives other than those manufactured by Valspar is not recommended.

Do not use for any other purpose other than as specified in our literature.

Safety Data

First Aid Instructions	For advice, contact the Poisons Information Centre on 131 126 (Australia), 0800 764 766 (New Zealand), or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If inhaled remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.
Safety Directions	Keep out of reach of children. Avoid contact with skin and eyes. Ensure adequate ventilation during use. Avoid prolonged breathing of vapour. Wash hands thoroughly after use.
Further Information	For the latest information refer to the Safety Data Sheet available on our websites. Australia: www.wattyl.com.au or contact Wattyl Assist on 132 101. New Zealand: www.wattyl.co.nz or contact Wattyl Assist on 0800 825 7727.

1. This information is provided with respect to the listed Wattyl products. Valspar Paint (Australia) recommends that:

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Valspar; (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the technical data sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy of its contents, Valspar cannot guarantee that the information is wholly comprehensive.

3. Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar Office.

4. To the full extent permitted by law, Valspar's liability for breach of a condition or warranty implied into the contract for sale between Valspar and you by law is limited at Valspar's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

Wattyl®, Interior Design i.d®, Aqua Prep®, Master Prep®, Colour Designer® & Ecotint® are registered trademarks of Valspar Paint (Australia) Pty Ltd ABN 40 000 035 914.

WATTYL ASSIST: Ph: 132 101 (AUSTRALIA)
Ph: 0800 825 7727 (NEW ZEALAND)