

HSNO 2017 - New Zealand

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : WATTYL FORESTWOOD TRADITIONAL OIL STAIN CHARCOAL  
Product identity : 813533  
Product type : Paint or paint related material

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : buildings  
Identified uses : Consumer applications, Professional applications, Used by spraying.

#### 1.3 Details of the supplier of the safety data sheet

Company details : Hempel (Wattyl) New Zealand Limited  
4-14 Patiki Road  
Avondale, Auckland 1026  
New Zealand  
Tel.: +(64) 98010034  
Email: wattyl@wattyl.com.au  
Date of Preparation : 3 May 2024  
Date of previous issue : 2 May 2024.

#### 1.4 Emergency telephone number

Emergency telephone number (with hours of operation)  
Poisons Centre New Zealand: 0800 764 766 (24 hour)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### GHS Classification

FLAMMABLE LIQUIDS - Category 3  
SKIN SENSITISATION - Category 1  
CARCINOGENICITY - Category 2  
REPRODUCTIVE TOXICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1  
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

#### 2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 - Flammable liquid and vapour.  
H317 - May cause an allergic skin reaction.  
H336 - May cause drowsiness or dizziness.  
H351 - Suspected of causing cancer.  
H361 - Suspected of damaging fertility or the unborn child.  
H372 - Causes damage to organs through prolonged or repeated exposure. (central nervous system (CNS))  
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements :

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not apply directly into or onto water. Take all reasonable steps to ensure that the substance does not cause any significant adverse effects to the environment beyond the application area.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor, mist or spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### SECTION 2: Hazards identification

Response :	Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage :	Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal :	Dispose of contents and container in accordance with all local, regional, national and international regulations.

### 2.3 Other hazards

Other hazards which do not result in classification : None known.

### SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	≥60 - ≤75
naphtha (petroleum), hydrodesulphurized heavy	64742-82-1	<10
triiron tetraoxide	1317-61-9	≤5
xylene	1330-20-7	<1
naphthalene	91-20-3	≤0.67
ethylbenzene	100-41-4	<1
2-butanone oxime	96-29-7	≤0.3
terbutryn	886-50-0	≤0.22
2-octyl-2H-isothiazol-3-one	26530-20-1	<0.1

Occupational exposure limits, if available, are listed in Section 8.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General :	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).
Eye contact :	Check for and remove any contact lenses. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. In all cases of doubt, or when symptoms persist, seek medical attention.
Inhalation :	Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.
Skin contact :	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion :	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.
Protection of first-aiders :	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

Eye contact :	No known significant effects or critical hazards.
Inhalation :	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact :	Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
Ingestion :	Can cause central nervous system (CNS) depression.

##### Over-exposure signs/symptoms

Eye contact :	No specific data.
---------------	-------------------

### SECTION 4: First aid measures

Inhalation :	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact :	Adverse symptoms may include the following: irritation redness dryness cracking
Ingestion :	No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician :	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments :	No specific treatment.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Extinguishing media :	Recommended: alcohol resistant foam, CO <sub>2</sub> , powders, water spray. Not to be used : waterjet.
-----------------------	------------------------------------------------------------------------------------------------------------

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :	Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products :	Decomposition products may include the following materials: carbon oxides metal oxide/oxides

#### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilt product.

#### 6.4 Reference to other sections

**SECTION 6: Accidental release measures**

See Section 1 for emergency contact information.  
 See Section 8 for information on appropriate personal protective equipment.  
 See Section 13 for additional waste treatment information.

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used.

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

**7.3 Specific end use(s)**

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

Product/ingredient name	Exposure limit values
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	<b>ACGIH TLV (United States).</b> TWA: 25 ppm 8 hours. TWA: 145 mg/m <sup>3</sup> 8 hours.
naphtha (petroleum), hydrodesulphurized heavy	<b>ACGIH TLV (United States).</b> TWA: 25 ppm 8 hours. TWA: 145 mg/m <sup>3</sup> 8 hours.
triiron tetraoxide	<b>Safe Work Australia (Australia, 10/2022). [Rouge dust]</b> TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Dust <b>Safe Work Australia (Australia, 10/2022). [Iron oxide]</b> TWA: 5 mg/m <sup>3</sup> , (as Fe) 8 hours. Form: Fume
xylene	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 4/2022). [xylene (o-, m-, p-isomers)] Ototoxicant.</b> WES-TWA: 50 ppm 8 hours. WES-TWA: 217 mg/m <sup>3</sup> 8 hours.
naphthalene	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 4/2022). Absorbed through skin.</b> WES-STEL: 10 mg/m <sup>3</sup> 15 minutes. WES-STEL: 2 ppm 15 minutes. WES-TWA: 2.6 mg/m <sup>3</sup> 8 hours. WES-TWA: 0.5 ppm 8 hours.
ethylbenzene	<b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 4/2022). Absorbed through skin. Ototoxicant.</b> WES-STEL: 176 mg/m <sup>3</sup> 15 minutes. WES-STEL: 40 ppm 15 minutes. WES-TWA: 88 mg/m <sup>3</sup> 8 hours. WES-TWA: 20 ppm 8 hours.

**Recommended monitoring procedures**

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**8.2 Exposure controls**

**Appropriate engineering controls**

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

### SECTION 8: Exposure controls/personal protection

#### Individual protection measures

General : Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.



- Hygiene measures : Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.
- Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Hand protection : Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.
- Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:
- Recommended: Silver Shield / Barrier / 4H gloves, nitrile rubber (>0.3 mm), polyvinyl alcohol (PVA), Viton®  
May be used: nitrile rubber (>0.1 mm)  
Short term exposure: neoprene rubber (>0.1 mm), butyl rubber (>0.5 mm), natural rubber (latex) (>0.4 mm), polyvinyl chloride (PVC), butyl rubber (>0.3 mm)
- Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.
- Respiratory protection : When the product is applied by spraying and for continuous or prolonged work always wear an air-fed respirator e.g. hood with supply of fresh or compressed air or a full face, powered air purifying filter. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. Be sure to use an approved/certified respirator or equivalent.

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

- Physical state : Liquid.
- Odour : Solvent-like
- pH : Testing not relevant or not possible due to nature of the product.
- Melting point/freezing point : -66°C This is based on data for the following ingredient: hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
- Boiling point/boiling range : Testing not relevant or not possible due to nature of the product.
- Flash point : Closed cup: 37°C (98.6°F)
- Evaporation rate : Testing not relevant or not possible due to nature of the product.
- Flammability : Not available.
- Lower and upper explosive (flammable) limits : 1.4 - 7.6 vol %
- Vapour pressure : 0.147 kPa This is based on data for the following ingredient: hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
- Vapour density : Testing not relevant or not possible due to nature of the product.
- Relative density : 0.84 g/cm<sup>3</sup>
- Partition coefficient (LogKow) : Testing not relevant or not possible due to nature of the product.
- Auto-ignition temperature : Testing not relevant or not possible due to nature of the product.

**SECTION 9: Physical and chemical properties**

Decomposition temperature : Testing not relevant or not possible due to nature of the product.  
Viscosity : Testing not relevant or not possible due to nature of the product.  
Explosive properties : Testing not relevant or not possible due to nature of the product.  
Oxidising properties : Testing not relevant or not possible due to nature of the product.

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability**

The product is stable.

**10.3 Possibility of hazardous reactions**

Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid**

Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**10.5 Incompatible materials**

**10.6 Hazardous decomposition products**

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides metal oxide/oxides

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

**Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LC50 Inhalation Vapour	Rat	6350 ppm	4 hours
	LD50 Dermal	Rabbit	>4200 mg/kg	-
naphthalene	LD50 Oral	Rat	3523 mg/kg	-
	LD50 Dermal	Rabbit	>20 g/kg	-
	LD50 Oral	Rat	490 mg/kg	-
ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
2-butanone oxime	LD50 Dermal	Rabbit	1001 mg/kg	-
	LD50 Oral	Rat	930 mg/kg	-
terbutryn	LD50 Dermal	Rabbit	>10200 mg/kg	-
	LD50 Oral	Rat	2045 mg/kg	-
2-octyl-2H-isothiazol-3-one	LC50 Inhalation Dusts and mists	Rat	0.58 mg/l	4 hours
	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-

**Irritation/Corrosion**

**SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Score	Exposure
xylene	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams
	Skin - Irritant	Rabbit	-	-
naphthalene	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams
	Skin - Severe irritant	Rabbit	-	24 hours 0.05 Milliliters
	Eyes - Mild irritant	Rabbit	-	-
ethylbenzene	Respiratory - Mild irritant	Rabbit	-	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams
	Eyes - Severe irritant	Rabbit	-	100 microliters
2-butanone oxime	Eyes - Moderate irritant	Rabbit	-	76 milligrams
	Skin - Mild irritant	Rabbit	-	380 milligrams
terbutryn	Eyes - Severe irritant	Rabbit	-	100 milligrams
	Skin - Severe irritant	Rabbit	-	-

**Sensitiser**

Product/ingredient name	Route of exposure	Species	Result
2-octyl-2H-isothiazol-3-one	skin	Mouse	Sensitising

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Category 3		Narcotic effects
naphtha (petroleum), hydrodesulphurized heavy	Category 3		Narcotic effects

**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Category 1	inhalation	central nervous system (CNS)
naphtha (petroleum), hydrodesulphurized heavy	Category 1	inhalation	central nervous system (CNS)
xylene	Category 2	-	-
naphthalene	Category 1	-	-
ethylbenzene	Category 2	-	-
2-butanone oxime	Category 2	-	-
terbutryn	Category 2	-	-

**Aspiration hazard**

Product/ingredient name	Result
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) naphtha (petroleum), hydrodesulphurized heavy	

**Information on likely routes of exposure**

Routes of entry anticipated: Oral, Dermal, Inhalation.

**Potential chronic health effects**

Sensitisation : Contains 2-butanone oxime, 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

Other information : No additional known significant effects or critical hazards.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Do not allow to enter drains or watercourses. Toxic to aquatic life with long lasting effects.

Product/ingredient name	Result	Species	Exposure
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Chronic EC50 4.6 - 10 mg/l	-	72 hours
	Chronic EC50 10 - 20 mg/l		48 hours
naphthalene	Chronic EC50 10 - 30 mg/l		96 hours
	Acute EC50 1600 µg/l Fresh water	-	48 hours
	Acute LC50 2350 µg/l Marine water		48 hours
ethylbenzene	Acute LC50 213 µg/l Fresh water		96 hours
	Chronic NOEC <1000 µg/l Fresh water	-	96 hours
	Acute EC50 2 µg/l Fresh water	-	72 hours
terbutryn	Acute EC50 7100 µg/l Fresh water		48 hours
	Acute LC50 0.82 mg/l Fresh water		96 hours
	Acute EC50 0.084 mg/l	-	72 hours
2-octyl-2H-isothiazol-3-one	Acute EC50 0.42 mg/l		48 hours

**SECTION 12: Ecological information**

	Acute LC50 0.036 mg/l	96 hours
--	-----------------------	----------

**12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	OECD 301F Ready Biodegradability - Manometric Respirometry Test	74.7 % - Readily - 28 days	-	-
naphtha (petroleum), hydrodesulphurized heavy	OECD 301F Ready Biodegradability - Manometric Respirometry Test	74.7 % - Readily - 28 days	-	-
xylene	OECD 301F Ready Biodegradability - Manometric Respirometry Test	90 - 98 % - Readily - 28 days	-	-
ethylbenzene	-	>60 % - Readily - 28 days	-	-
		>70 % - Readily - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	-	-	Readily
naphtha (petroleum), hydrodesulphurized heavy	-	-	Readily
xylene	-	-	Readily
ethylbenzene	-	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	-	10 - 2500	high
naphtha (petroleum), hydrodesulphurized heavy	-	10 - 2500	high
xylene	3.12	8.1 - 25.9	low
naphthalene	3.4	36.5 - 168	low
ethylbenzene	3.6	-	low
2-butanone oxime	0.63	2.5 - 5.8	low
terbutryn	3.74	-	low
2-octyl-2H-isothiazol-3-one	2.45	507 - 538	high

**12.4 Mobility in soil**

Soil/water partition coefficient (K<sub>oc</sub>): No known data available in our database.

Mobility: No known data available in our database.

**Other adverse effects**

No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

**Packaging**

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.



# Safety Data Sheet






## WATTYL FORESTWOOD TRADITIONAL OIL STAIN CHARCOAL

**wattyl**<sup>®</sup>

A part of  HEMPEL

### SECTION 14: Transport information

Transport may take place according to national regulation NZS for transport by road and train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env.*	Additional information
<b>NZS Class</b>	UN1263	PAINT	3  	III	Yes.	<b>Hazchem code</b> •3Y
<b>IMDG Class</b>	UN1263	PAINT. (hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))	3  	III	Yes.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Emergency schedules</b> F-E, S-E
<b>IATA Class</b>	UN1263	PAINT	3 	III	Yes.	The environmentally hazardous substance mark may appear if required by other transportation regulations.

PG\* : Packing group

Env.\* : Environmental hazards

#### 14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Transport in bulk according to IMO instruments

Not applicable.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

#### HSNO Classification

FLAMMABLE LIQUIDS - Category 3

SKIN SENSITISATION - Category 1

CARCINOGENICITY - Category 2

REPRODUCTIVE TOXICITY - Category 2

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

Safety, health and environmental regulations specific for the product :

No known specific national and/or regional regulations applicable to this product (including its ingredients).

HSNO Group Standard :

HSR002669

HSNO Group Standard assigned are based upon the GHS Classification.

### SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Classification	Justification
FLAMMABLE LIQUIDS - Category 3 SKIN SENSITISATION - Category 1 CARCINOGENICITY - Category 2 REPRODUCTIVE TOXICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

Notice to reader

### SECTION 16: Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.