

1.4 Emergency telephone number

HSNO 2017 - New Zealand

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name :	WATTYL GRANOSITE GRANOPRIME
Product identity :	852001
Product type :	Paint or paint related material

1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application :	buildings
Identified uses :	Consumer applications, Professional applications, Used by spraying.

1.3 Details of the supplier of the safety data sheet

Company details :	Hempel (Wattyl) New Zealand Limited 4-14 Patiki Road	Emergency telephone number (with hours of operation)	
	Avondale, Auckland 1026 New Zealand Tel.: +(64) 98010034 Email: wattyl@wattyl.com.au	Poisons Centre New Zealand: 0800 764 766 (24 hour)	
Date of Preparation :	24 February 2025		
Date of previous issue	20 February 2025.		

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition :	Mixture
GHS Classification	
LONG-TERM (CHRONIC) AQUATI	C HAZARD - Category 2

2.2 Label elements

Hazard pictograms :



No signal word.
H411 - Toxic to aquatic life with long lasting effects.
Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not apply directly into or onto water. Take all reasonable steps to ensure that the substance does not cause any significant adverse effects to the environment beyond the application area.
Avoid release to the environment.
Collect spillage.
Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 Other hazards

Other hazards which do not result None known. in classification :

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%
zinc pyrithione	CAS: 13463-41-7	<0.1

Occupational exposure limits, if available, are listed in Section 8.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.



SECTION 4: First aid measures

4.1 Description of first aid measures

General :	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
	If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).
Eye contact :	Check for and remove any contact lenses. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. In all cases of doubt, or when symptoms persist, seek medical attention.
Inhalation :	Remove to fresh air.
Skin contact :	Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Remove contaminated clothing and shoes.
Ingestion :	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.
Protection of first-aiders :	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects	
Eye contact :	No known significant effects or critical hazards.
Inhalation :	No known significant effects or critical hazards.
Skin contact :	May cause an allergic skin reaction.
Ingestion :	No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Eye contact :	No specific data.
Inhalation :	No specific data.
Skin contact :	Adverse symptoms may include the following: irritation redness
Ingestion :	No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

 Notes to physician :
 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

 Specific treatments :
 No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media :	Recommended: alcohol resistant foam, CO ₂ , powders, water spray.
	Not to be used : waterjet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :	In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products :	Decomposition products may include the following materials: carbon oxides metal oxide/oxides

5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13).

6.4 Reference to other sections

See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Product/ingredient name	Exposure limit values
No exposure limit value known.	

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Individual protection measures

General :

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.



Hygiene measures :

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.



Method

SECTION 8: Exposure controls/personal protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.
Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:
Recommended: Silver Shield / Barrier / 4H gloves, nitrile rubber (>0.3 mm), neoprene rubber (>0.1 mm), butyl rubber (>0.5 mm), natural rubber (latex) (>0.4 mm), polyvinyl chloride (PVC), Viton®, nitrile rubber (>0.1 mm), butyl rubber (>0.3 mm) Short term exposure: polyvinyl alcohol (PVA)
Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.
U se a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. (EN140) Be sure to use an approved/certified respirator or equivalent.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state :	Liquid.						
Odour :	Non-characteristic.	Non-characteristic.					
pH :	7 - 9						
Melting point/freezing point :	Testing not relevant or n	ot possible	due to natur	e of the product	-		
Boiling point/boiling range :	Testing not relevant or n	ot possible	due to natur	e of the product			
Flash point :	Closed cup: 101°C (213.	.8°F)					
Evaporation rate :	Testing not relevant or n	Testing not relevant or not possible due to nature of the product.					
Flammability :	Not available.						
Vapour pressure :	Vapour Pressure at 20°C				Vap	our pressu	re at 50°C
	Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Metho
	water	17.5	2.3				

Vapour density :

Specific gravity :

Partition coefficient (LogKow) : Auto-ignition temperature :

Decomposition temperature :

Viscosity :

Explosive properties : Oxidising properties :

9.2 Other information

Solvent(s) % by weight : Water % by weight : VOC content : TOC Content : Solvent Gas :

Weighted average: 1 % Weighted average: 55 % 0.84 g/l Weighted average: 7 g/l Weighted average: 0.001 m³/l

Not available.

Not available.

1.3 g/cm³

Testing not relevant or not possible due to nature of the product.

Testing not relevant or not possible due to nature of the product.

Kesstimatico (40%) and out a vatilable bible due to nature of the product.

Testing not relevant or not possible due to nature of the product.

Testing not relevant or not possible due to nature of the product.



SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

No specific data.

10.5 Incompatible materials

Reactive or incompatible with the following materials: acids.

10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed: Decomposition products may include the following materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

No known significant effects or critical hazards.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure	Effects
zinc pyrithione	Rat - Oral - LD50 Rat - Dermal - LD50 Rat - Inhalation - LC50 Dusts and mists	269 mg/kg >2000 mg/kg 1.03 mg/l [4 hours]	

Irritation/Corrosion

No known data avaliable in our database.

Sensitiser

No known data avaliable in our database.

Mutagenic effects

No known data avaliable in our database.

Carcinogenicity

No known data avaliable in our database.

Reproductive toxicity

No known data avaliable in our database.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Not available.			

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
zinc pyrithione	Category 1	-	-

Aspiration hazard

Product/ingredient name	Result	1
Not available.		



SECTION 11: Toxicological information

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential chronic health effects

No known significant effects or critical hazards.

Other information : No additional known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Do not allow to enter drains or watercourses. Very toxic to aquatic life with long lasting effects.

Product/ingredient name	Result	Species	Exposure
zinc pyrithione	Acute - LC50	Fish	0.0026 mg/l [96 hours]
	Acute - EC50	Daphnia	0.0082 mg/l [48 hours]
	Acute - EC50	Algae	0.0012 mg/l [120 hours]

12.2 Persistence and degradability

Product/ingredient name	Test			Result	
Not available.					
Product/ingredient name	Aquatic half-life	Pho	tolysis		
zinc pyrithione				Inherent	

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
zinc pyrithione	0.9	11	Low

12.4 Mobility in soil

Product/ingredient name	logKoc	Кос
2-benzisothiazol-3(2H)-one	1.86	73.142
5-chloro-2-methyl-2H-isothiazol-3-one	1.72	52.9944
2-methylisothiazol-3(2H)-one	1.74	54.9187

Mobility :

No known data avaliable in our database.

Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

Transport may take place according to national regulation NZS for transport by road and train, IMDG for transport by sea, IATA for transport by air.



SECTION 14: Transport information

	14.1 UN no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env*	Additional information
NZS Class	Not regula	ated.	-	-	No.	Hazchem code -
IMDG Class	Not regula	ated.	-	-	No.	-
IATA Class	Not regula	ated.	-	-	No.	-

PG* : Packing group

Env.* : Environmental hazards

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

HSNO Classification

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

Safety, health and environmental regulations specific for the product :

No known specific national and/or regional regulations applicable to this product (including its ingredients).

HSNO Group Standard :

HSR002670

HSNO Group Standard assinged are based upon the GHS Classification.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Classification	Justification
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	Calculation method

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.